

Unit 1 - 21 Orchard Rd Brookvale NSW Australia 2100

Ph: 61 2 99050383

Email: <a href="mailto:info@bourkevalves.com.au">info@bourkevalves.com.au</a>
Web: <a href="mailto:www.bourkevalves.com.au">www.bourkevalves.com.au</a>

## SOFT SEAT SAFETY VALVE 15mm (1/2)

Soft Seat Safety Relief Valve of the highest quality and performance. Designed and manufactured in accordance with Australian Standards 1271, and suitable for most pressure vessels.

Designation of Bourke Valves part number.

Example : SS - 15 - 1035 - BSP

Thread Standard (BSP) Pressure setting in kPa

Thread Size

Valve type – SS (Soft Seat)

## **FEATURES INCLUDE:**


- Ring lift manual override.
- Atmospheric discharge.
- Bubble Tight seal.



## TECHNICAL DATA

BOURKE PART NO.	SS - 15 - #
Size - BSP	15mm (1/2)
Pressure setting - #	242-1380 kPa (35-200 PSI)
Temperature Rating(Max.)	120°C
Height - mm	80
Weight - grams	160
Body & Cap	Brass
Stem	Brass
Seal Retainer	Brass
Sealing member	O'Ring
	(Nitrile, Viton, EPDM)
Spring	Stainless Steel
Keyring	Stainless Steel

## FLOW RATE CHART



# Specify Pressure Setting required

Discharge Capacity measured at 10% over set pressure

Every valve is factory tested for crack and reseal performance. Specifications are subject to change without notice.

Proudly Australian Made



Australian Owned